

TORQUE WRENCHES

for  Tornado®



Why should I use a torque wrench?

While setting a tool it is extremely important to tighten it appropriately.

If not effectively tight indeed a cutting tool could slide away from the tool holder during the working process. On the other side, an excessive tightening can cause damages to the tool holder or spring collet or the tool itself.



How to use

Turn the handle to choose the correct torque power based on the router bits diameter. While tightening with constant action a strong shot is perceived both mechanically and acoustically. This indicates that the tightening torque is reached.

| Item | Type | Nm (Ø) | (Ft/lb) | Nm (Ø) | (Ft/lb) | L |
|------------|-----------------|------------|---------|-------------|---------|-----|
| Z052.722.N | DIN6499 (ER25) | 55 (Ø2-5) | 40 | 90 (Ø6-16) | 66 | 480 |
| Z052.723.N | DIN6499 (ER32) | 70 (Ø1-6) | 51 | 130 (Ø7-20) | 95 | 480 |
| Z052.724.N | DIN6499 (ER40) | 120 (Ø2-7) | 88 | 200 (Ø8-30) | 147 | 480 |
| Z052.728.N | DIN6499 (EOC25) | 120 (Ø2-8) | 88 | 200 (Ø9-25) | 147 | 480 |



WEBSITE

